

DS-ProCapture-X

POE Fingerprint Access Control Terminal



DS-ProCapture-X is a POE fingerprint access control terminal with the most advanced SilkID technology, which not only possesses outstandingly high identification rate towards dry, wet and rough finger, but also provides the utmost security with its live finger detecting capability. The device is designed in horizon style design and is equipped with touch keypad, which provides a superior touching experience. It also offers flexibility standalone installation or with any third-party access control panel that supports standard wiegand signal. TCP/IP, RS485 and Wi-Fi (Optional) are available that the device can be used in different networks.

FEATURES

- Modern design and interactive user interface.
- Multiple Verification Modes: Fingerprint / Card / Password.
- Outstanding performance with dry, wet, and rough fingers.
- Revolutionary Silk ID Fingerprint Sensor.
- Wireless Network: WI-FI Connection.

SPECIFICATIONS

MAIN SPECIFICATIONS

- » Fingerprint Capacity 20,000 templates
- » Transaction Capacity 500,000 templates
- » Card Capacity 50,000 templates
- » Hardware 1.2GHz high speed CPU 128mb RAM 256mb Flash
Hi-Fi Voice & Indicator
Tamper Switch Alarm
- » Communication TCP/IP, USB-host, RS485
- » Sensor BioID Fingerprint sensor
- » Wiegand Signal Input & Output
- » Power 12VDC 3A, <500mA
- » Operating Temperature -10°C~40°C
- » Dimension 200.5 x 88.5 x 28.7 mm
- » Compatibility ZKBioSecurity Software
Wiegand Slave Reader

STANDARD FUNCTIONS

- » Groups/Holidays/DST
Bell-schedule/Duress Mode
(Password)/Anti-passback
Record Query/Custom
Wallper & ScreenSaver/
Access Levels
- » Multiple Verification Modes
Alive Finger Detection

OPTIONAL FUNCTIONS

- » Fingerprint Card
- » ZK Encrypted Card (optional)

APPLICATIONS



CORPORATE AND GOVERNMENT OFFICES



PUBLIC TRANSPORT FACILITIES



SCHOOL AND UNIVERSITIES



BANKS AND HOTELS

CONNECTION DIAGRAM

