



# DS-ProlD

# **RS485 Series Reader**





The ProID-RS family of card readers is designed to offer card technologies options to customers such as 125KHz EM, 13.56MHz MIFARE, DESFire.

With a robust all-weather protection and a beautiful modern design, the ProID-RS family is the best choice for indoor or outdoor applications.

#### **FEATURES**

- High stability and energy efficiency.
- Rapid facial recognition within 0.3s.
- EED light and touch keypad.
- RS485 output.
- Waterproof design suitable for indoor or outdoor applications.
- Black or white color available.

#### **SPECIFICATIONS**

» Index Protection

#### MAIN SPECIFICATIONS

» Read Range ≥5cm» Reading Time ≤300ms

» Input Port External LED & Buzzer Control

» Supported Panel InBio 160 Pro, 260 Pro, 460 Pro

**IP65** 

» Output Format RS485» Material ABS+PC

» Power 7~13V DC, <80mA

» Operating Temperature 10% ~ 90% Relative Humidity

Non-Condensing

» Dimension ProID20/30-RS: 90 × 90 × 16mm.

» Audio Beep

#### STANDARD FUNCTIONS

**OPTIONAL FUNCTIONS** 

#### **ProID RS-485 Reader List**

ProID20 BE-RS	ProID20 BM-RS	ProID20 WE-RS	ProID20 WM-RS	ProID20 BD-RS
ProID20 WD-RS	ProID30 BE-RS	ProID30 BM-RS	ProID30 WE-RS	ProID30 WM-RS

### **How to Order ProID Series?**

## ProID20 WE - RS





