

DS-ProID

Physical Access Readers



The DS-ProID family of card readers is designed to offer card technologies options to customers such as 125KHz EM, 13.56MHz MIFARE, DESFire, FeliCa or Legic.

With a robust all-weather protection and a beautiful modern design, the DS-ProID family is the best choice for indoor or outdoor applications.

FEATURES

- High stability and energy efficiency.
- On-site adjustable Wiegand output (26 or 34 bits).
- LED light and touch keypad.
- RS485 output.
- Waterproof design suitable for indoor or outdoor applications.
- Black or white color available.

SPECIFICATIONS

MAIN SPECIFICATIONS

» Read Range	≥3.5cm / 5cm
» Reading Time	≤300ms
» Input Port	External LED & Buzzer Control
» LED	Pulsing White Standby Light Red and Green LEDs
» Output Format	RS485
» Material	ABS+PC
» Index Protection	IP65
» Power	7~13V DC, <80mA
» Operating Temperature	10% ~ 90% Relative Humidity Non-Condensing
» Dimension	ProID10: 80.5 × 44 × 15mm. ProID20/30: 90 × 90 × 16mm. ProID40: 116 × 75 × 15mm.
» Audio	Beep

STANDARD FUNCTIONS

OPTIONAL FUNCTIONS

How to Order ProID Series?

ProID20 WE-RS

