

DS-ProRF-T

RFID Access Control Terminal



DS-ProRF-T is an RFID access control terminal incorporated with 2.4 inches TFT LCD Screen .The color display and new firmware structure offer a user-friendly menu for easy management, as well as photo taking capability that enables attendance photos and photo ID (optional). The new ZMM 220 hardware platform has a clock rate of 1.2 GHZ, greatly enhancing the speed verification. Touch keypad enables easy and convenient operations, such as managing users, accessing control parameter settings, or reading reports.

FEATURES

- Modern Design & Interactive UI
- Simple Management & Scalability
- Multiple Verification Modes: Card / Password
- Built In Camera:
 - * Event Snapshot
 - * User Photo (Optional)
- Touch Keypad

SPECIFICATIONS

MAIN SPECIFICATIONS

» Hardware	1.2GHz High Speed CPU Memory 128MB RAM/1256MB Flash
» Transaction Capacity	100,000 templates
» Card Capacity	50,000 templates
» User Photos	3,000 templates
» Event Photos	7,000 templates
» Display	2.4 Inches TFT-LCD Screen
» Communication	TCP/IP, USB-host
» Wiegand Signal	Input & Output
» Power	12VDC, <500mA
» Operating Temperature	-10°C~50°C
» Dimension	195.5 × 87 × 35 mm.
» Compatibility	Wiegand Slave Reader ZKBioSecurity

STANDARD FUNCTIONS

- » Access Levels / Groups / Holidays/ DST / Bell Schedule
- Duress Mode (Password) / Anti-Passback / Record Query / Custom Wallpaper & Screen Saver

OPTIONAL FUNCTIONS

- » User Photo
- » ZK Encrypted Card

APPLICATIONS



CORPORATE AND GOVERNMENT OFFICES



PUBLIC TRANSPORT FACILITIES



SCHOOL AND UNIVERSITIES



BANKS AND HOTELS

CONNECTION DIAGRAM

